



## Induction cookers Tehma

**TMI** series

Large stylish glass-ceramic touch panel

The sensor works even with wet or greasy hands.

13 modes of regulation by temperature or by power.



Increased coil diameter and increased power!

Uniform dense winding.

Maximum temperature 240°C

Maximum power: 3,5kW Faster heating and cooking.

All information about temperature, power and timer is displayed on the digital screen.



Timer with touch control for 24 hours

3-layer aluminum air filters

Easy to remove and install.

Can be washed in a dishwasher.





The cooking surface is made of ceramic tempered glass.

Holds up to 50 liters per burner.

The ceramic glass surfaces of the burners and the control panel are made at the same level as the stove body.

All joints are reliably protected by a silicone layer for complete sealing against moisture and dirt.



2 fans for each burner for stable long-term operation







Wide range of input voltage: from 200 to 240 V.

Stable operation even during strong voltage drops









### Uniform dense winding

### Increased coil diameter





### 3-layer aluminum air filter



Easy access to remove and install Can be washed in the dishwasher





## Additional fans for each burner on the back panel



### **Induction cookers Tehma**

#### **Features**

- Modern design;
- A shelf for storing dishes;
- 3-layer aluminum air filters;
- Additional fans for cooling each burner;
- Size of burner is 300x300mm;
- Maximum load on the burner 50 L;
- Hull made of food-grade stainless steel;
- Work surface made of glass ceramics;
- A ledge above the control panel protects against shocks and dirt;
- 24-hour timer;
- Convenient control panel with touch control of power and temperature from 60 to 240°C (400 – 2800/3500 W) – 13 levels;
- The surface joints of the burner and the control panels are protected with a special silicon against moisture and dirt;
- adjustable legs;
- Protection against overheating, protection against objects accidentally left on the burner, automatic detection of dishes.









### Handheld

### Technical characteristics of handheld

#### TMI series cookers



Characteristic	1 burner TMI28H1 / TMI35H1	2 burners TMI28H2 / TMI35H2
Power of 1 burner	2,8 / 3,5 kW	2,8 / 3,5 kW
Voltage	220 V	220 V
Number of temperature modes	13	13
Range of temperature modes	60 – 240°C	60 – 240°C
Timer	Up to 24 hours	Up to 24 hours
Size of the burner	300x300 mm	300x300 mm
Length	365 mm	710 mm
Width	445 mm	445 mm
Height	110 mm	110 mm

### Induction cooker 1 burner TMI28H1 (2,8 kW) / TMI35H1 (3,5 kW)

- Overall dimensions: 365x445x110mm
- Power: 2,8kW (max 2,8kW) / 3,5kW(max 3,5kW)









### Induction cooker 2 burners TMI28H2 (2,8 kW) / TMI35H2 (3,5 kW)

• Overall dimensions: 710x445x110mm

Power: 2,8kW(max 5,6kW) / 3,5kW(max 7kW)











### Modular

### Technical characteristics of modular

#### TMI series cookers



Characteristic	2 burners TMI28M2 / TMI35M2	4 burners TMI28M4 / TMI35M4	4 burners Thin TMI28M4T / TMI35M4T	6 burners TMI28M6 / TMI35M6
Power of 1 burner	2,8 / 3,5 kW	2,8 / 3,5 kW	2,8 / 3,5 kW	2,8 / 3,5 kW
Voltage	380 V	380 V	380 V	380 V
Number of temperature modes	13	13	13	13
Range of temperature modes	60 – 240°C	60 – 240°C	60 – 240°C	60 – 240°C
Timer	Up to 24 hours	Up to 24 hours	Up to 24 hours	Up to 24 hours
Size of the burner	300x300 mm	300x300 mm	300x300 mm	300x300 mm
Length	400 mm	800 mm	1500 mm	1100 mm
Width	700 / 800 / 900 mm	700 / 800 / 900 mm	600 mm	700 / 800 / 900 mm
Height	850 mm	850 mm	850 mm	850 mm

#### **Induction cooker 2 burners**

TMI28M2 (2,8 kW) / TMI35M2 (3,5 kW)



- Overall dimensions: 400x700x850 / 400x800x850 / 400x900x850mm
- Power: 2,8kW(max 5,6kW) / 3,5kW(max 7kW)







### **Induction cooker 4 burners**

TMI28M4 (2,8 kW) / TMI35M4 (3,5 kW)



- Overall dimensions: 800x700x850 / 800x800x850 / 800x900x850mm
- Power: 2,8kW(max 11,2kW) / 3,5kW(max 14kW)







### Induction cooker 4 burners, Thin

TMI28M4T (2,8 kW) / TMI35M4T (3,5 kW)

• Overall dimensions: 1500x600x850mm

Power: 2,8kW(max 11,2kW) / 3,5kW(max 14kW)









#### **Induction cooker 6 burners**

TMI28M6 (2,8 kW) / TMI35M6 (3,5 kW)



Power: 2,8kW(max 16,8kW) / 3,5kW(max 21kW)









### Temperature modes

Induction cookers of the TMI series

### For 2.8 kW models



Режим	1	2	3	4	5	6	7	8	9	10	11	12	13
Power Watt	400	600	800	1000	1200	1400	1600	1700	1800	2000	2400	2600	2800
Temperature °C	60	80	100	120	130	140	150	160	170	180	200	220	240

### For 3.5 kW models

Режим	1	2	3	4	5	6	7	8	9	10	11	12	13
Power Watt	400	600	800	1000	1200	1400	1600	1800	2100	2400	2800	3200	3500
Temperature °C	60	80	100	120	130	140	150	160	170	180	200	220	240





# The Tehma company has been operating on the market for 20 years The total manufacturing area is 15000m<sup>2</sup> More than 300 employees





